

Stand Base/Stand Clamp Helicoidal Jacks

RCA/RC
HCS-H

RCA/RC

RoHS

Catalog
Code

W6081

The base allows for posts to be positioned close together with the magnet of the clamps.



Application
Systems

Optics &
Optical
Coatings

Opto-
Mechanics

Bases

Manual
Stages

Actuators &
Adjusters

MotORIZED
Stages

Light Sources &
Laser Safety

Index

Guide

Vibration
Isolation Systems

Optical Tables

Darkrooms/
Dark Boxes


Optical Bases

Posts

Brackets


Adapters

Tools



Outline Drawing

RCA




Part Number	A (mm)
RCA-M16	M16 P1
RCA-M6	M6
RCA-1/4UU	1/4-20UNC

RC-10*-17/25

Hexagon socket head cap screw (stainless steel construction) M6x15...1 screws, Flat washer

RC-10*-17UU/25UU

Hexagon socket head cap screw (stainless steel construction) 1/4-20UNCx5/8...1 screws, Flat washer



Part Number	A (mm)	B (mm)
RC-10-17/RC-10A-17	42	17
RC-10-25/RC-10A-25	50	25

Specifications

Primary material: Stainless Steel (RC-10A-**: Aluminium)
Finish: None (RC-10A-**: Black Anodized)

Part Number	Product Name	To hold	Mounting	Weight [kg]
RCA-M16	Stand Base	M16 Rod Stand	Magnet, Stand Clamp (RC-10)	0.023
RCA-M6	Stand Base	M6 Rod Stand	Magnet, Stand Clamp (RC-10)	0.035
RCA-1/4UU	Stand Base	1/4 INCH Rod Stand	Magnet, Stand Clamp (RC-10)	0.035
RC-10-17	Stand Base	Stand Base (RCA-M16)	Hexagon socket head bolt M6x15	0.027
RC-10A-17	Stand Base	Stand Base (RCA-M16)	Hexagon socket head bolt M6x15	0.009
RC-10-25	Stand Base	Stand Base (RCA-M16)	Hexagon socket head bolt M6x15	0.031
RC-10A-25	Stand Base	Stand Base (RCA-M16)	Hexagon socket head bolt M6x15	0.011
RC-10-17UU	Stand Base	Stand Base (RCA-1/4UU)	Hexagon socket head bolt 1/4-20UNCx5/8	0.027
RC-10-25UU	Stand Base	Stand Base (RCA-1/4UU)	Hexagon socket head bolt 1/4-20UNCx5/8	0.031
RC-10A-17UU	Stand Base	Stand Base (RCA-1/4UU)	Hexagon socket head bolt 1/4-20UNCx5/8	0.009
RC-10A-25UU	Stand Base	Stand Base (RCA-1/4UU)	Hexagon socket head bolt 1/4-20UNCx5/8	0.011

HCS-H

RoHS

Catalog
Code

W6047

Coarse adjustment Helicoidal Jack with 15 mm of Travel

- The upper plate moves upward without rotating.
- The helicoid screw system, provides 15mm/rotation of smooth movement.



Example of Combinations




Helicoidal jack connected to a post holder.

Outline Drawing

HCS-H

Hexagonal socket head cap screw M4x8...4 screws



Specifications

Primary material: Aluminum
Finish: Black Anodized

Part Number	Load Capacity [N]	Weight [kg]
HCS-H	19.6 (about 2.0kgf)	0.45