

Magnet Base Flexible Post Holder

MB
MB-MX/MX-AM

MB

RoHS

Catalog
Code

W6027

These bases can secure optical components to any flat magnetic bench.



- The magnet is activated by switching the lever ON/OFF.
- Does not require tapped holes for attachment.
- The tapped holes on the top surface can be metric or inch depending on the model.

Guide

► A SP-130 adapter can be used to attach stages to the surface of the MB-CB-PB bases. ► [WEB Reference](#) [Catalog Code](#) W6072


[Reference](#) D045

► The opposite surface of the ON/OFF switching lever of MB-PG is also magnetized.




Outline Drawing



MB-S40





MB-L40





MB-CB-PB





MB-BUU





MB-L65C-M4



MB-L65A-M6





MB-L65C-M6EE / MB-L65C-1/4UU





Part Number	A (mm)	B
MB-L65C-M6EE	25	M6 P1
MB-L65C-1/4UU	25.4	1/4-20UNC


MB-PH




MB-PG



MB-L120-M4



MB-L120-M6





Specifications			
Part Number		Holding Force [N]	Weight [kg]
MB-S40	—	198 (about 20kgf)	0.4
MB-L40	—	49 (about 5kgf)	0.2
MB-CB-PB	MB-BUU	294 (about 30kgf)	1
MB-L65C-M4	—	198 (about 20kgf)	0.5
MB-L65C-M6EE	MB-L65C-1/4UU	198 (about 20kgf)	0.6
MB-L65A-M6	—	198 (about 20kgf)	0.6
MB-PH	—	490 (about 50kgf)	2.5
MB-PG	—	490 (about 50kgf)	2.4
MB-L120-M4	MB-L120-M6	294 (about 30kgf)	2.4

RoHS **Catalog** **Code** **W6038**



- The cam style clamping mechanism can easily be locked and unlocked with the turn of the knob.
- The post clamp is designed to securely hold $\phi 12$ posts.
- The MB-MX has a magnetic base and can be freely secured on flat magnetic surfaces.
- The MX-AM has an external thread M16P1 on the bottom. It can be directly secured to base plates.



Specifications		
Part Number	Holding Force*	Weight [kg]
MB-MX	1.96N (about 0.2kgf)	1.9
MX-AM	1.96N (about 0.2kgf)	0.9

WEB <http://www.sigma-koki.com/english/> **E-mail** international@sigma-koki.com **TEL** +81-3-5638-8228 **FAX** +81-3-5638-6550

Tools

D029