OSDOTS



The OSDOTS series (Overhead Table Systems) is used for mounting vibration producing equipment above the laboratory bench. The height of shelf can be easily adjusted. Shelves can be positioned at any position along the rail.



- Convenient location of instruments.
- Increased table space.

Table Length+235

550

400 (200×2)

- Mechanical isolation of equipments with fans.
- Overhead shelf adjusted in height, dree standing.
- Leveling feet for uneven floors.
- Formed steel welded design, black power coat finished.
- Additional shelfing units are available.(Optional).
- Goiunded-electrical outlets (110V / 220V / 60Hz) on each side of the shelf.

1940H 1905H

Min

500

• N.F.B (30A) for preventing instruments from overload currency.



Outline Drawing

Manual Stages

Bases

Actuators & Adjusters

Application Systems

Optics & Optical Coatings

Opto-Mechanics

Motoeized Stages

Light Sources & Laser Safety

Index

Guide

Vibration Isolation Systems

Optical Tables

Darkrooms/ Dark Boxes

Optical Bases

Posts

Brackets

Adapters

Tools

Specifications	
Part Number	Weight [kg]
OSDOTS-4	106
OSDOTS-5	128
OSDOTS-6	135
OSDOTS-7	157
OSDOTS-8	164
OSDOTS-10	193
OSDOTS-12	249

660

Æ

į,

950

550

150

WEB http://www.sigma-koki.com/english/ E-mail international@sigma-koki.com TEL +81-3-5638-8228 FAX +81-3-5638-6550