



Travel: 25mm or more


SHS2-25




SHN2-25




MHN2-25M



SHN2-40



SHH2-50



Attention

► Depending on the stage type, there is the possibility of shortened travel or interference with mounting parts. Contact our Sales Division when you swapping micrometer heads.

Specifications

Part Number	Travel [mm]	Type	Readable Resolution [mm]	Lead of Actuator [mm]	Load Capacity (Static load) [N]	Weight [kg]
SHS2-25	0 - 25	Small diameter	0.01	0.5	39.2 (4kgf)	0.05
SHN2-25	0 - 25	Standard	0.01	0.5	39.2 (4kgf)	0.09
MHN2-25M	0 - 25	Digital display	0.001	0.5	39.2 (4kgf)	0.235
SHN2-40	0 - 40	Small diameter	0.01	0.5	39.2 (4kgf)	0.12
SHH2-50	0 - 50	Standard	0.01	0.5	39.2 (4kgf)	0.23

Application Systems

Optics & Optical Coatings

Opto-Mechanics

Bases

Manual Stages

Actuators & Adjusters

MotORIZED Stages

Light Sources & Laser Safety

Index

Micrometer Heads

Differential Micrometer Heads

Fine-pitch Screws

Remote

PKA

ACT